

Indian National Trust for Art and Cultural Heritage
(INTACH , 71 , KK Birla Lane , Lodhi Estate , New Delhi -110003,
Ph. No. 011-49854100

TENDER NOTICE

No. 2/Lift/INTACH/2018

08.03.2018

Sealed quotations are invited for replacing the existing Hydraulic Passenger Lift in the office premises of INTACH building at 71, Lodhi Estate, New Delhi with a new one. The tender forms containing detailed terms and conditions can be obtained from our website www.intach.org and E-mail admhicci@gmail.com.

2. The capacity of the lift will be 10 passengers, 680 kgs. Total number of stoppage/ Landings will be 05 stops / 05 openings. Travel height (in meters) will be 10.900m approximately.
3. Terms and Conditions & Technical data sheet and standard features of the lift are enclosed at Annexure I & II.
4. The space in which the lift is to be installed may be inspected any working day i.e. Monday to Friday between 10.00 am to 5.00 pm.
5. The firm should have sufficient experience in installing the lifts in the Govt. offices/ PSUs and Private offices. Besides this, the firm should be the OEM (original equipment Manufacturer) and have sound financial background. The list of the clients may also be enclosed.
6. The firm is required to adhere to the safety norms fixed by the Govt. from time to time and have sufficient spare parts available to replace the faulty parts.
7. Sealed quotations should be sent to the Director (Admin.), INTACH at 71, Lodhi Estate, New Delhi on or before by 19th March 2018 by 12:00 noon. Quotations will be opened at 4:00pm on the same day. INTACH has the absolute right to reject the quotations without assigning any reason.

(Director Admin)
INTACH

Terms and Conditions

1. The tender will be on a two bid systems 1) Technical Bid. 2) Financial Bid. Please ensure that the Technical Bid and Financial Bid is submitted in two different sealed envelopes and these should be put in an outer envelope super scribed with tender no. date of opening and item name .

2. The validity of bid will be 60 days from the date of opening and the rates will be valid upto the end of financial year 2017-18 year from the date of opening of Agreement.

Tenderer should submit:-

- a. Affidavit that the company has not been blacklisted any time for quoting and supplying for the item in schedule by any government organization affidavit should be on non judicial stamp paper of Rs. 10 & attested by Notary Public/Oath commissioner.
- b. The copy of valid GST Registration Certificate.
- c. The document proof of similar works done in last three years i.e. one work amounting to Rs. 10 Lacs in one year or two works of more than Rs. 20 Lacs in any last three years in CPWD/MES/Autonomous body or any other Government Department. (Performance reports to be enclosed).

Technical Data Sheet

| | |
|--|---|
| Model | |
| Type of elevator | Gearless & Machine Room less |
| Number of passengers | 10 |
| Rated load | 680 kg |
| Number of Stops | 5 |
| Number of Entrances | 5 |
| Number of access sides | 1 |
| Minimum Floor to Floor height (required) | 2600mm |
| Lockable storage room (required) | 250 Sq. Ft. |
| Stilt area under roof (required) | 200 Sq. Ft. |
| Floor Designations | |
| Travel height | 10,900m |
| Headroom height | 4,600mm from last landing finished floor level |
| Lintel Height (required) | 2180mm from finished floor level |
| Clear Inside Shaft (available) | 1,800 mm Width x 1,800 mm Depth |
| Pit depth | 1,500 mm |
| Drive System | Variable Voltage Variable Frequency Controlled |
| Type of Controller | Full Collective control – Simplex |
| Speed of travel | 1.00 m/s |
| Car Size | 1,200mm (W) x 1,400 mm (D) x 2135 mm (H) |
| Door Width | 800 mm |
| Door Height | 2000 mm |
| Door Opening Direction | Center opening |
| Car Design | |
| | <ul style="list-style-type: none"> • Car Walls in Stainless steel hairline finish • Car door in glass with Stainless Steel Hairline finish Frame • Natural granite flooring – Black Sea |
| Landing Doors | |
| | <ul style="list-style-type: none"> • Fully automatic landing doors in Glass Stainless steel hairline finish frame |
| Standard Features | |
| | <ul style="list-style-type: none"> • 2 Hours Fire rated landing doors • Automated Rescue Device • Overload • Pre –announcing arrows for collective controls • Position Indicator |

| | |
|-------------------------|---|
| | <ul style="list-style-type: none">• Light curtain protection on doors• Car and Landing operating panel in touch sensitive, stylish, resistant glass panel.• Door open/ close and alarm buttons• Visual and acoustic confirmation of call• Call acceptance (Visual)• Battery operated alarm bell.• Emergency light |
| Special Features | |
| | <ul style="list-style-type: none">• Auto car light off• Protection against Power Fluctuation• Intercom between car and lobby |